

Interior Finishes

- 1 1/4" quartz countertops in kitchen and bathrooms
- 42" upper cabinets with choice of colour and style from our suppliers (Maple, Melamine or Thermafoil)
- Full depth cabinet over fridge Soft close cabinets in kitchen
- Pot and pan drawers
- \$5000 credit for appliances Backsplash in kitchen
- Single border row ceramic tile around tubs and shower
- Mirrors full width of vanity
- Semi-frameless single shower door

- Choice of standard package
- bathroom hardware
- Tile floors in wet areas
- Laminate flooring on main level Carpet on upper level and stairs • 8lb carpet underlay
- 3 hinges on all interior doors
- Swing doors on closets
- Round or square vertical drywall corners California Knockdown ceilings
- Paint or stain on railings
- Unfinished basement stairs



Electric, Heating & Plumbing

- 4 LED lights on main floor
- 2 pendant lights in kitchen 1 electric fireplace
- 100 amp electrical service with 60 breaker capacity
- 220V service to dryer and range
- Decor light switches and outlets
- Island outlet as per plan
- Soffit outlet with switch GFI protection in all bathrooms
- 3 GFI exterior weatherproof outlets
- Arc fault protection outlets for bedrooms Structured wiring run into mechanical room
- Rough in central vacuum
- Wired smoke and CO detectors Programmable thermostat
- Forced air heating with drip humidifier Gas line to main kitchen
- HRV or bath fan
- Furnace and ducts power vacuumed prior to possession
- Waterline to fridge
- Floor drain at laundry location
- Shut off valves to all toilets and sinks
- 1 soaker tub in master bath

9' foundation wall height
 9' main floor ceiling height

Structural & Concrete

- 18 x 8" MPA concrete footing Basement walls
- 8" thick, 10mm rebar, 20 MPA concrete
- Floors are 3 1/2" thick poured over 6 mil poly and washed rock
- Asphalt emulsion spray to damp roof of the exterior foundation
- Weeping tile around perimeter with 6" of washed rock • Garage floor has 10mm rebar with reinforced 24" on center and piles Concrete driveways
- Poured sidewalk to front step piles or brackets with 10mm reinforcement

Exterior, **Doors &** Windows

- Fibreglass exterior doors
- Half glass/rear garden door
 57 x 33" slider
- basement windows
- Steel insulated garage door
- Belt driven garage door opener with 2 remotes and keyless entry

Framing

system Roof trusses 24" on

- centre 18" overhang
- Tongue and grooved OSB
- subfloor, glued & screwed • 3/8" OSB on roof with H clips
- 3/8" spruce underlay in
- tile areas
- Wood framed basement walls 24" on center
- 2 x 6 spruce stud exterior
- walls, 3/8" OSB walls
- 25 year warranty on
- asphalt shingles

Energy Efficient Features

- High efficiency single
- stage furnace
- Low flush toilets •
- Low flow taps and
- shower heads
- Insulated rim joists
- around perimeter
- R-40 fibreglass insulation in attic
- R-20 insulation on all floors
- Insulated exterior door Windows are PVC integral
- frame with jamb
- 587-524-1131 | sales@activehomes.ca

Standard Spec Features | 2024

ActiveHomes.ca

This design is published by Active Homes I to fall rights reserved inclu ding the reproduction in whole

Engineered floor and truss