BETTE

ACTIVE

Front Attached 24' | Single-Family Home

Features


- 9' Ceilings
- Quartz Countertops
- Side Entrance
- Main Floor Full Bath
- Mudroom
- Main Floor Bedroom / Den
- Open to Above Great Room
- Upper-Floor Laundry
- Attached Double Garage
- Spice Kitchen



Bedrooms


3 Baths

[2,066 Total Sq. Ft.] 481 Garage Sq. Ft.



966 Main Floor Sq. Ft.

1,100 Upper Floor Sq. Ft.



587-524-1131 | sales@activehomes.ca

ActiveHomes.ca



Interior Finishes

- 1 1/4" quartz countertops in kitchen and
- · 42" upper cabinets with choice of colour and style from our suppliers (Maple, Melamine or Thermafoil)
- Full depth cabinet over fridge
- Soft close cabinets in kitchen
- Pot and pan drawers \$5000 credit for appliances
- · Single border row ceramic tile around tubs and shower
- · Mirrors full width of vanity
- Semi-frameless single shower door

- · Choice of standard package
- · bathroom hardware

File floors in wet areas · Laminate flooring on main level Carpet on upper level and stairs • 8lb carpet underlay

- 3 hinges on all interior doors
- Swing doors on closets
- · Square vertical drywall corners California Knockdown ceilings
- · Paint or stain on railings with Iron spindles
- · Painted basement stairs



Electric, Heating & Plumbing

- · 4 LED lights on main floor
- · 3 pendant lights in kitchen
- 1 electric fireplace
- 150 amp electrical service with 60 breaker capacity
- 220V service to dryer and range Decor light switches and
- · 2 Island outlet as per plan
- · Soffit outlet with switch
- GFI protection in all bathrooms
- · 3 GFI exterior weatherproof outlets
- Arc fault protection outlets for bedrooms Structured wiring run into mechanical room
- Rough in central vacuum
- Wired smoke and CO detectors Programmable thermostat
- Forced air heating with drip humidifier Gas line to main kitchen
- Furnace and ducts power vacuumed prior to possession
- · Waterline to fridge
- Floor drain at laundry location Shut off valves to all toilets and sinks
- · 1 soaker tub in master bath
- · Garage heater rough in

Strutural & Concrete

- 9' foundation wall height
 9' main floor ceiling height
 18 x 8" 25 MPA concrete footing Basement walls
- 8" thick, 10mm rebar, 20 MPA concrete
- Floors are 3 1/2" thick poured over 6 mil poly and
- Asphalt emulsion spray to damp roof of the
- exterior foundation
- Weeping tile around perimeter with 6" of washed rock · Garage floor has 10mm rebar with reinforced 24" on center and piles Concrete driveways
- Poured sidewalk to front step piles or brackets with 10mm reinforcement

Exterior, Doors & **Windows**

- Fibreglass exterior doors
- Half glass/rear garden door57 x 33" slider
- basement windows
- Fiber insulated garage door
- · Belt driven garage door opener with 2 remotes and keyless entry

Framing

- · Engineered floor and truss system Roof trusses 24" on centre 18" overhang
- Tongue and grooved OSB subfloor, glued & screwed
- 3/8" OSB on roof with H clips
- 3/8" spruce underlay in
- tile areas 24"
- Wood framed basement walls on center
- 2 x 6 spruce stud exterior walls, 3/8" OSB walls
- 25 year warranty on asphalt shingles

Energy Efficient **Features**

- · High efficiency single stage furnace
- Low flush toilets
- Low flow taps and
- shower heads
- Insulated rim joists
- around perimeter
- R-40 fibreglass insulation

- R-20 insulation on all floors Insulated exterior door
- Windows are PVC integral frame with jamb
- Triple Pane Window

Standard Spec Features | 2024

587-524-1131 | sales@activehomes.ca

ActiveHomes.ca