

Interior Finishes

- 1 1/4" quartz countertops in kitchen and bathrooms
- 42" upper cabinets with choice of colour and style from our suppliers (Maple, Melamine or Thermafoil)
- Full depth cabinet over fridge
- Soft close cabinets in kitchen
- Pot and pan drawers
 \$5000 credit for appliances
- Single border row ceramic tile around tubs and shower
- Mirrors full width of vanity
- Semi-frameless single shower door

- Choice of standard package
- bathroom hardware
- Tile floors in wet areas
- Laminate flooring on main level Carpet on upper level and stairs
- 8lb carpet underlay
- 3 hinges on all interior doors
- Swing doors on closets
- Square vertical drywall corners California Knockdown ceilings
- Paint or stain on railings with Iron spindles
- Painted basement stairs



Electric, Heating & Plumbing

- 4 LED lights on main floor
- 3 pendant lights in kitchen
- 1 electric fireplace150 amp electrical service with 60 breaker capacity
- 220V service to dryer and range Decor light switches and outlets
- 2 Island outlet as per plan
- Soffit outlet with switch
- GFI protection in all bathrooms
- 3 GFI exterior weatherproof outlets
- Arc fault protection outlets for bedrooms Structured wiring run into mechanical room
- Rough in central vacuum
- Wired smoke and CO detectors Programmable thermostat
- Forced air heating with drip humidifier Gas line to main kitchen
- Bath fan
- Furnace and ducts power vacuumed prior to possession
- Waterline to fridge
- Floor drain at laundry location
- Shut off valves to all toilets and sinks
- 1 soaker tub in master bath
 Garage heater rough in
- Garage neater rough in

Structural & Concrete

• 9' foundation wall height

- 9' main floor ceiling height
- 18 x 8" 25 MPA concrete footing Basement walls
 8" thick, 10mm rebar, 20 MPA concrete
- 8 chick, 10mm repar, 20 MPA concrete
 Floors are 3 1/2" thick poured over 6 mil poly and washed rock
- Asphalt emulsion spray to damp roof of the
- exterior foundation
- Weeping tile around perimeter with 6" of washed rock
 Garage floor has 10mm rebar with reinforced 24" on center and piles Concrete driveways
- Poured sidewalk to front step piles or brackets with 10mm reinforcement

Exterior, Doors & Windows

- Fibreglass exterior doors
- Half glass/rear garden door
 57 x 33" slider
- basement windows
- Fiber insulated garage door
 Belt driven garage door
 opener with 2 remotes and
 keyless entry

Framing

• Engineered floor and truss system Roof trusses 24" on centre 18" overhang

- Tongue and grooved OSB
- subfloor, glued & screwed • 3/8" OSB on roof with H clips
- 3/8" spruce underlay in
- tile areas 24"
- Wood framed basement walls on center
- 2 x 6 spruce stud exterior walls, 3/8" OSB walls
- 25 year warranty on
- asphalt shingles

Energy Efficient Features

- High efficiency single stage furnace
- Low flush toilets
- Low flow taps and
- shower heads
- Insulated rim ioists
- around perimeter
- R-40 fibreglass insulation
- in attic
- R-20 insulation on all floors
- Insulated exterior door
- Windows are PVC integral
- frame with jamb

 Triple Pane Window

Standard Spec Features | 2024

587-524-1131 | sales@activehomes.ca

ActiveHomes.ca

This design is published by Active Homes Ltd., all rights reserved, including the reproduction in whole or in part. Dimensions, square footage and details shown are approximate and may be subject to change wil